



NOTES:

- MATERIAL:
 BODY:LCP, BLACK, UL 94V-0
 TERMINAL:COPPER ALLOY , T=0.10mm
 SHELL:STAINLESS STEEL
- FINISH:
 TERMINA:50U" NI UNDERPLATED OVER ALL
 GOLD FLASH ON CONTACT AREA
 TIN 60-200U" PLATING ON SOLDERTAIL AREA
 SHELL:50U" NI MIN UNDERPLATED OVER ALL
 AU 1-3U" PLATING ON SOLDERTAIL AREA
- GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD.
- ALL DIMENSIONS MARKED ∇ MUST BE CONTROLLED BY QC
- ALL DIMENSIONS MARKER \textcircled{XX} MUST BE MEASURE BY FAI.

D	E1908499A	调整尺寸管控	08/30/2019	UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
C	E1707196A	成品端子改善	07/06/2017	DATE: 06/21/2016	X. ± 0.25	X." $\pm 5.00'$	CHECKED:	TITLE: 1.5H 测压式的Battery
B	E1608314A	修改图面与实物一致	08/04/2016	SCALE: 10:1	.XX ± 0.10	.XX" $\pm 1.00'$	APPROVE:	DRAWING NO:
A		NEW	06/21/2016	SHEET: 1/1	MATERIAL:		昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE			