


- NOTES:
- MATERIAL:
BODY: LCP, BLACK, UL 94V-0
TERMINAL: COPPER ALLOY C5240, T=0.10mm
SHELL: STAINLESS STEEL
 - FINISH:
TERMINAL: 50U" NI UNDERPLATED OVER ALL
GOLD FLASH ON CONTACT AREA
TIN 60-200U" PLATING ON SOLDER TAIL AREA
SHELL: 50U" NI MIN UNDERPLATED OVER ALL
AU 1-3U" PLATING ON SOLDER TAIL AREA
 - Rated Current: 2A/PIN MIN
 - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 - ALL DIMENSIONS MARKER (XX) MUST BE MEASURED BY FAI.
 - GP PASSED ACCORD WITH HRD-ROHS-219 STANDARD

H	E1908499A	调整尺寸公差	08/30/2019	UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: B55-AB03F15A
G	E1810492A	成品端子头 折弯尺寸管控更新	11/03/2018	DATE: 01/07/2015	X. ±0.25	X° ±5.00°	CHECKED:	NAME: 1.5H side pressure Battery
F	E1709311A	修改尺寸标注位置	09/11/2017	SCALE: 10:1	.XX ±0.10	.XX° ±1.00°	APPROVE:	DRAWING NO: A-B55-0000_H
E	E1703040A	增加折弯尺寸管控	03/06/2017	SHEET: 1/1	.XXX ±0.05	.XXX° ±0.50°	 昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE			