



NOTES:  
 1. MATERIAL:  
 BODY:HI-TEMP. PLASTIC, BLACK, UL 94V-0  
 TERMINAL:COPPER ALLOY, T=0.12mm  
 SHELL:STAINLESS STEEL T=0.10mm  
 2. GP PASSED ACCORD WITH RoHS STANDARD.  
 3. FINISH:  
 TERMINAL:50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON CONTACT AREA  
 TIN 60-200u" PLATED ON SOLDER TAIL AREA  
 SHELL:50u" Ni MIN UNDER PLATING OVER ALL  
 AU 1~3u" PLATED ON SOLDER TAIL AREA  
 4. ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC.  
 ALL DIMENSIONS MARKED (XX) MUST BE MEASURED BY FAI.

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
C	E1511448A	修改塑胶与铁壳 卡点处结构	11/18/2015	DATE: 11/18/2015	X. ±0.25	X." ±2.00'	CHECKED:	B30-AB03F15C
B	E1506229A	主体加护位 改善端子变形	06/12/2015	SCALE: 10:1	.X ±0.10	.X' ±1.00'	APPROVE:	TITLE: 1.50H 侧压式 3PIN Battery 2.50PITCH
A		NEW	09/26/2014	SHEET: 1/1	.XXX ±0.05	.XXX' ±0.10'		DRAWING NO:
REV.	ECN NO.	DESCRIPTION	DATE	REV. C	MATERIAL:		FINISH: SEE NOTE	

