



NOTES:
 1.MATERIAL:
 BODY:HI-TEMP. PLASTIC,BLACK,UL 94V-0
 TERMINAL:C7035,T=0.20mm
 SHELL:SUS304 T=0.15mm
 2.FINISH:
 TERMINA:
 50u" Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH ON CONTACT AREA
 60-200u" TIN PLATED ON SOLDERTAIL AREA
 SHELL:
 50u" Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH PLATED ON SOLDERTAIL AREA
 3.ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 4.Resistance: 25mΩ MAX.

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
				DATE: 05/10/2014	X. ±0.20	X' ±2.00'	CHECKED:	B39-AB03F19A
				SCALE: 10 / 1	.X ±0.15	.X' ±1.00'	APPROVE:	TITLE: BAATTERY 1.90H
B	E1405114A	铁壳改镀金	05/10/2014	SHEET: 10 / 1	.XX ±0.10	.XX' ±0.50'		DRAWING NO:
A		NEW	01/22/2014	SHEET: 1 / 1	MATERIAL:			
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE			

