



T-CARD PIN NO.	PIN NO.
T1	DAT2
T2	CD/DAT3
T3	CMD
T4	VDD
T5	CLK
T6	VSS
T7	DATO
T8	DAT1
SIM CARD PIN NO.	PIN NO.
P1-A/B	VCC
P2-A/B	RST
P3-A/B	CLK
P5-A/B	GND
P6-A/B	VPP
P7-A/B	I/O

NOTES:
 1. MATERIAL:
 HOUSING: LCP, BLACK, UL 94V-0
 CONTACT: PHOSPHOR BRONZE, T=0.15MM
 SHELL: STAINLESS STEEL T=0.20MM
 2. FINISH:
 CONTACT: 50U' NI MIN PLATING OVER ALL
 1U' AU ON THE CONTACT AREA AND
 SOLDER AREA
 SHELL: SELECTIVE 1U' AU ON SOLDER TAIL AREA
 50U' NI MIN. PLATING OVER ALL
 3. ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 4. ALL DIMENSIONS MARKED (XX) MUST BE MEASURED BY FAI

REV.	ECN NO.	DESCRIPTION	DATE	REV.	A	FINISH: SEE NOTE
H	E1712456A	弹高加高0.03mm	12/22/2017	UNITS: mm	GENERAL TOLERANCE	
G	E1707213A	改善防溃pin	07/14/2017	DATE: 06/09/2014	X. ±0.25	X° ±5.00°
F	E1707189A	设为防溃pin结构	07/03/2017	SCALE: 4:1	.X ±0.15	.X° ±3.00°
E	E1606212A	修改图面与实物相符 增加FAI序号	06/14/2016	SHEET: 1/1	.XX ±0.10	.XX° ±1.00°
					.XXX ±0.05	.XXX° ±0.50°

RECOMMENDED PCB LAYOUT
 GENERAL TOLERANCE ± 0.05

